

# Towards a manifold learning in parametric RTM processes. A geometric approach.

N.Montes <sup>1a)</sup>, C.Ghniatos <sup>2b)</sup>, H.Tertrais <sup>3c)</sup>, J.L.Duval <sup>4d)</sup>, E.Abisset-Chavanne <sup>3e)</sup>,  
A.Falco <sup>1f)</sup> and F.Chinesta <sup>3g)</sup>

<sup>1</sup>ESI Chair @ University CEU Cardenal Herrera. C/San Bartolomé 55, Alfara del Patriarca, Valencia Spain.

<sup>2</sup>Notre Dame University-Louaize, Mechanical Engineering Department, Zouk Lebanon.

<sup>3</sup>ESI Chair @ ENSAM ParisTech. 151 Boulevard de l'Hopital, 75013 Paris, France

<sup>4</sup>ESI Group parc Icade Immeuble le Séville, 3 bis, Saarinen, CP 50229, 94528 Rungis Cedex

<sup>a)</sup>Corresponding author: nicolas.montes@uchceu.es

<sup>b)</sup> cghnatos@ndu.edu.lb, <sup>c)</sup> hermine.tertrais@ec-nantes.fr, <sup>d)</sup> Jean-Louis.Duval@esi-group.com,

<sup>e)</sup> emmanuelle.abisset-chavanne@ec-nantes.fr, <sup>f)</sup> afalco@uchceu.es

<sup>g)</sup> Francisco.chinesta@ensam.eu

**Abstract.** This work aims at providing a parametric solution of LCM processes, and in particular RTM, when the location of the injection gate is assumed being problem parameter. It is well known that parameters can be easily considered as model extra-coordinates within the Proper Generalized decomposition framework. Then, the use of separated representations allows efficiently circumventing the curse of dimensionality, and then calculating very efficiently the so-called computational vademecums that contain all the solutions of the problem at hand for any choice of the material, process or geometrical parameters. The interested reader can refer to the reviews [2, 3, 4, 5, 6] and the numerous references therein. However, even if the construction of such parametric solutions within the PGD rationale is nowadays in most of cases mature, using both intrusive [6] or non-intrusive [1] approaches, the last approach induces spurious solutions when interpolating solutions exhibiting localization. The present paper shows a parametric geometric approach for RTM processes where the injection gate is a parameter. It allows to move the inlet in real-time and to determine the effect that the inlet position has in the filling process. At the end of the papers, some numerical examples are shown.

## References

- [1] D. Borzacchiello, J.V. Aguado, F. Chinesta. Non-intrusive sparse subspace learning for parametrized problems. Arch. Comput. Methods Eng., In press.
- [2] F. Chinesta, P. Ladeveze, E. Cueto. A short review in model order reduction based on proper generalized decomposition. Arch. Comput. Methods Eng., 18, 395-404, 2011.
- [3] F. Chinesta, A. Leygue, F. Bordeu, J.V. Aguado, E. Cueto, D. Gonzalez, I. Alfaro, A. Ammar, A. Huerta. PGD-based computational vademecum for efficient design, optimization and control. Arch. Comput. Methods Eng., 20, 31-59, 2013.
- [4] F. Chinesta, R. Keunings, A. Leygue. The Proper Generalized Decomposition for Advanced Numerical Simulations. A primer. Springerbriefs, Springer, 2014.
- [5] F. Chinesta, P. Ladeveze (Edts). Separated Representations and PGD Based Model Reduction: Fundamentals and Applications. CISM-Springer, 2014.

- [6] F. Chinesta, A. Huerta, G. Rozza, K. Willcox. Model Order Reduction. Chapter in the Encyclopedia of Computational Mechanics, Second Edition, Erwin Stein, Ren\_e de Borst & Tom Hughes Edt., John Wiley & Sons Ltd., 2015.
- [7] E. Lopez, D. Gonzalez, J. V. Aguado, E. Abisset-Chavanne, E. Cueto, C. Binetruy, F.Chinesta. A manifold learning approach for integrated computational materials engineering. Arch. Computat. Methods Eng., 25, 59-68, 2018.
- [8] S.T. Roweis, L.K. Saul. Nonlinear dimensionality reduction by Locally Linear Embedding Science, 290, 2323-2326, 2000.