

# Experimental and numerical investigation of the contact behavior during FE forming simulation of continuously reinforced composites in wet compression moulding

Christian Poppe<sup>1,a</sup>, Dominik Dörr<sup>1</sup>, Fabian Kraus, Luise Kärger<sup>1</sup>

<sup>1</sup>Karlsruhe Institute of Technology, Institute for Vehicle System Technology, Chair of Light-Weight Technology, Rintheimer-Querallee 2, 76131 Karlsruhe, Germany

a) Corresponding author: [christian.poppe@kit.edu](mailto:christian.poppe@kit.edu)

**Keywords:** FE-Forming Simulation, Wet compression moulding, Contact characterisation, and -modelling

**Abstract.** Wet compression moulding (WCM) provides large-scale production potential for continuously fiber reinforced structural components as a promising alternative to resin transfer moulding (RTM). Lower cycle times are possible due to the parallelization of the process steps draping, infiltration and curing during moulding (viscous draping). Experimental and theoretical investigations indicate and prove strong mutual dependencies between the physical mechanisms, especially between resin and laminate [1-3]. However, significant cavity pressures develop only towards the end of the tool stroke, when the cavity is almost filled with either resin or fibres. Thus, the resin's impact on the draping behaviour (intra-ply and interface behaviour) is of great interest since it represents a large part of the draping process [3]. Regarding the investigation and modelling of the tangential contact behaviour, several studies [4-7] show that on a macroscopic scale, rate-, pressure- and viscosity dependent material models need to be applied for both thermoplastic and thermoset based processes. Beyond that, it needs to be questioned whether the assumption of a compressive stress condition within the contact does always apply. In fact it strongly depends on the investigated geometry, used material model and the process conditions whether this assumption holds true. This has not yet been investigated properly, not least because no characterisation methods regarding the normal contact behaviour under tension are yet available.

Therefore, experimental results on dry and infiltrated woven fabrics are presented, which confirm rate-, pressure- and viscosity-dependent tangential contact behaviour within the viscous draping process step (WCM). Based on a parametrisation of these results, FE forming simulation is utilized to assess and evaluate the process relevance on part level. Beyond that, investigations on the contact condition (pressure or tension) are presented to evaluate the relevance of more expensive characterisation and modelling approaches regarding the contact behaviour in normal direction.

## REFERENCES

1. Bergmann J., Dörmann H., Lange R., "Interpreting process data of wet pressing process. Part 1: Theoretical approach", Journal of composite materials Vol. 50, pp. 2399-2407 (2016)
2. Bergmann J., Dörmann H., Lange R., "Interpreting process data of wet pressing process. Part 2: Verification with real values", Journal of composite materials Vol. 50 (2016)
3. Poppe C, Dörr D, Henning F, Kärger L: "Experimental and numerical investigation of the shear behaviour of infiltrated woven fabrics", Composite Part A, Vol 14, 327-337, 2018 <https://doi.org/10.1016/j.compositesa.2018.08.018>
4. Sachs U.; Akkerman, R.; Fetfatsidis K.; Vidal-Sallé E.; Schumacher J.; Ziegmann G.; Allaoui S.; Hivet G.; Maron B.; Vanclooster K.; Lomov S. V., "Characterization of the dynamic friction of woven fabrics - Experimental methods and benchmark results", Composite Part A, V67, 289-298, 2014, doi: 10.1016/j.compositesa.2014.08.026
5. Fetfatsidis A.; Sherwood A., Chen Julie, Jauffres David, "Characterization of the fabric/tool and fabric/fabric friction during the thermostamping process", Int J Mater Form (2009) Vol. 2 Suppl 1:165-168, doi: 10.1007/s12289-009-0591-9
6. Hüttl J., Poppe C., Albrecht F., "Investigations on friction behaviour and forming simulation of plain woven fabrics for wet compression moulding", conference contribution, Proceedings SAMPE Europe, Stuttgart, Germany 2017
7. Dörr D., Faisst M., Joppich, T., Poppe, C., Henning, F., Kärger, L.; Modelling approach for anisotropic inter-ply slippage in finite element forming simulation of thermoplastic UD-tapes, API Conference Proceedings 1960, 020005 (ESAFROM, 2018), <https://doi.org/10.1063/1.5034806>